



Synchronous Chip Sealer

Bitumen and aggregate are commonly used materials in the road construction , and they can play a very good effect when combined with each other. But when spreading these materials, Bitumen distributor, dump truck and chip spreader are usually needed, which will increase the cost and is not convenient to manage. Synchronous chip sealer can load and spread three materials at the same time use one truck, which can effectively save the construction cost and improve the efficiency.



INTRODUCE
Road Maintenance Equipment
One-Stop Service


 SLTS0505

 SLTS0610

 SLTS0812

 SLTS0814

Model	SLTS0505	SLTS0610	SLTS0812	SLTS0814 (Fiber type)
Chassis	JAC 4*2	HOWO/SHACMAN 6*4	HOWO/SHACMAN 8*4	HOWO/SHACMAN 8*4
Aggregate bin volume	5m3	10-12m3	12-14m3	12-14m3
Bitumen tank volume	5m3	6m3	8m3	8m3
Aggregate diameter	3-25mm	3-25mm	3-25mm	3-25mm
Paving width	200-3800mm	200-3800mm	200-3800mm	200-4000mm
Amount of bitumen spread	0.2-3kg/m2	0.2-3kg/m2	0.2-3kg/m2	0.2-3kg/m2
Amount of aggregate spread	2-22L/m2	2-22L/m2	2-22L/m2	2-22L/m2
Bitumen heating rate	≥20℃/h	≥20℃/h	≥20℃/h	≥20℃/h
Best construction speed	3-6km/h	3-6km/h	3-6km/h	3-6km/h
Fiber cut length	--	--	--	30(mm)、60(mm)、120(mm)
Fiber spreading amount	--	--	--	30~90(g/m2)
Dimensions	8160*2550*3550(mm)	10220×2550×3850(mm)	11950×2500×3950(mm)	12000*2550*4000mm